

# AGRI-VATOR & ATTACHMENTS SPECIFICATIONS

## AGRI-VATOR

## AG 72

## AG96

## AG144

WEIGHT	1630 lbs	2045 lbs	2825 lbs
WORKING WIDTH		96"	144"
CENTER DRIVE GEARBOX	1:1.5 Tee	1:1.5 Tee	1:1.5 Tee
END DRIVE	3 Cx Belts (Left End)	2 Cx Belts (Both Ends)	3 Cx Belts (Both Ends)
TINE VIBRATION FREQUENCY	@ 540 PTO RPM = 1026 Cycles/Min	@ 540 PTO RPM = 1026 Cycles/Min	@ 540 PTO RPM = 1026 Cycles/Min
SIDE-TO-SIDE TINE TRAVEL	2 1/4 inches	2 1/4 inches	2 1/4 inches
VIBRATING DEPTH	6 inches	6 inches	6 inches
AERATION DENSITY	5 Holes per Sq. Ft	5 Holes per Sq. Ft	5 Holes per Sq. Ft
TINES	3/4 X 6" Forged And Hardened (144)	3/4 X 6" Forged And Hardened (192)	3/4 X 6" Forged And Hardened (288)
ROTOR BEARINGS	Double Sealed Tapered Roller	Double Sealed Tapered Roller	Double Sealed Tapered Roller
DRIVE LINE	1 3/8" Spline w/ Safety Shield	1 3/8" Spline w/ Safety Shield	1 3/8" Spline w/ Safety Shield
FINISH	Black Acrylic w Grey Trim	Black Acrylic w Grey Trim	Black Acrylic w Grey Trim

### CLEATED ROLLER

WEIGHT	(Approx) 570 LBS	(Approx) 650 LBS	(Approx) 1075 LBS
DIAMETER	12"	12"	12"

### SEEDER

WEIGHT	(Approx) 627 LBS	(Approx) 685 LBS	(Approx) 902 LBS
HOPPER CAPACITY	9 Bu	12 Bu	18 Bu
RATE CONTROL	Micro Flute Adjustment / Seed Cup	Micro Flute Adjustment / Seed Cup	Micro Flute Adjustment / Seed Cup
GAUGE MECHANISM	Interchangeable Sprockets	Interchangeable Sprockets	Interchangeable Sprockets
OUTLETS	12	16	24